



NEO

NAX

BEAVER TAIL SPREAD AXLE

STANDARD FEATURES

- INTEGRATED INLINE TONGUE, 2 5/16" COUPLER
- 24" ATP STONEGUARD
- ALL ALUMINUM, BONDED EXTERIOR SKIN
- 16" ON CENTER ROOF, SEAMLESS ALUMINUM
- 16OC FLOOR, 3/4" EXT GRD PLYWOOD
- 16OC WALLS, WHITE VINYL
- EXTRUDED ROUND TOP COVE
- LED LIGHTING, 2 INTERIOR DOMES
- 36" FLUSHLOCK CURBSIDE DOOR
- CAST ALUMINUM HOLDBACKS(SIDE DOOR)
- SELF ADJUSTING BRAKES, EZ LUBE HUBS
- AERODYNAMIC 90* V-NOSE
- NXP STAINLESS STEEL LATCH, RAMP DOOR
- ALUMINUM GRAB HANDLE(RAMP ONLY)
- ALUMINUM FENDERETTES
- PROEDGE, TAPERED RAMP DOOR EDGE
- RADIAL TIRES 225 75 R15 SILVER MOD RADIALS
- TIEDOWNS; 4 HEAVY DUTY D RINGS
- 8.5'W; 4' BEAVER TAIL, 6' ON 26' & 28'
- 5200# TORSION AXLES, SPREAD 42"
- 9990 GVWR

PRICE AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. OPTIONS ADDED TO BASE UNITS DECREASE PAYLOAD CAPACITY.

NAX 11.10.23



The Specs

Model	Axles	Tongue Ht.	Int. Ht.	Box Length	CS Door	Rear Door
NAX 2085R	2-5200#	22"	80.25"	20'	36"	92"W x 76.25"H
NAX 2285R	2-5200#	22"	80.25"	22'	36"	92"W x 76.25"H
NAX2485R	2-5200#	22"	80.25"	24'	36"	92"W x 76.25"H
NAX2685R	2-5200#	22"	80.25"	26'	36"	92"W x 76.25"H

6000# Torsion
Axles: Optional



For Additional Specs & Photos, go to:
neomfg.com

e-mail: sales@neomfg.com
21900 US 12 Sturgis, MI 49091
269.503.7630